



LYFTÖGLA MED HÅL EL KLAS 8

EXCEL

Lyftögla med hål EL Excel

Material: Seghärtningsstål klass 8. Får ej värmebehandlas. Säkerhetsfaktor: 5:1.
Ytbehandling: Lackerade.



Artnr	18251-0107	18251-0206	18251-0305	18251-0404
Typ	EL6R	EL8R	EL10R	EL12R
Max. last	0.20 ton	0.40 ton	0.70 ton	1.00 ton
a	M6 x 1.00 mm	M8 x 1.25 mm	M10 x 1.50 mm	M12 x 1.75 mm
b	31 mm	31 mm	31 mm	39 mm
c	51 mm	51 mm	51 mm	56 mm
d	29 mm	29 mm	29 mm	31 mm
e	14 mm	14 mm	14 mm	15 mm
f	44 mm	44 mm	44 mm	48 mm
g	11 mm	11 mm	11 mm	12 mm
h	6 mm	6 mm	6 mm	7 mm
Vikt	0.15 kg	0.15 kg	0.15 kg	0.23 kg

Artnr	18251-0503	18251-0602	18251-0701	18251-0800
Typ	EL14R	EL16R	EL18R	EL20R
Max. last	1.20 ton	1.50 ton	2.00 ton	2.50 ton
a	M14 x 2.00 mm	M16 x 2.00 mm	M18 x 2.50 mm	M20 x 2.50 mm
b	39 mm	44 mm	44 mm	44 mm
c	56 mm	66 mm	66 mm	66 mm
d	31 mm	36 mm	36 mm	36 mm
e	15 mm	17 mm	17 mm	17 mm
f	48 mm	60 mm	60 mm	60 mm
g	12 mm	14 mm	14 mm	14 mm
h	7 mm	9 mm	9 mm	9 mm
Vikt	0.23 kg	0.40 kg	0.40 kg	0.40 kg

Artnr	18251-0909	18251-1006	18251-1105
Typ	EL22R	EL24R	EL30R
Max. last	3.00 ton	4.00 ton	6.00 ton
a	M22 x 2.50 mm	M24 x 3.00 mm	M30 x 3.50 mm
b	52 mm	52 mm	66 mm
c	81 mm	81 mm	98 mm
d	47 mm	47 mm	56 mm
e	21 mm	21 mm	24 mm
f	75 mm	75 mm	88 mm
g	17 mm	17 mm	21 mm
h	11 mm	11 mm	14 mm
Vikt	0.63 kg	0.63 kg	1.11 kg